

SINCE



1952

PAINTS FOR INDUSTRY

ULTRA-BOND®

ACID ETCHING
METAL CONDITIONER

A water reducible, acid etching metal cleaner designed to remove dirt, grease, protective oils, and other contaminants from any metal surface. Ultra-Bond® cleans and conditions the substrate, preventing corrosion and promoting maximum coating adhesion by allowing paint to bond directly to the surface, creating a durable and long lasting finish.

- ✓ Acid etching formula
- ✓ Improves coating adhesion & durability
- ✓ Removes grease & protective oils
- ✓ Water reducible
- ✓ VOC compliant

Revised May 2024

DIRECTIONS FOR USE

Ultra-Bond® is the recommended cleaning solution for structural steel, tubing, wrought iron, and other metal surfaces. This product will significantly improve paint adhesion on galvanized, aluminum, and other nonferrous metals.

Application: Apply by spray, wipe, or dip, and allow material to sit for 15-30 minutes. Thoroughly wipe the surface clean with rags or shop towels to remove any loose powder that forms. Paint treated surface within 48 hours of application to prevent the formation of new rust.

TECHNICAL DATA

Appearance	Light blue
Volume Solids	6.50%
Weight Solids	10.25%
Weight per Gallon	8.7 lbs.
VOC	339 g/L (2.83 lbs/gal)
Shelf Life	1 year unopened
Packaging	1 gallon and 5 gallon containers

ADDITIONAL INFORMATION

Warning: this product is acidic and can cause skin and eye irritation or damage. Use appropriate personal protective equipment, including hand, eye, and face protection when using this product. This product is intended for professional industrial use only. Thoroughly review the product label and Safety Data Sheet before using. Product information, including the SDS and a copy of this PDS is available online at www.pfiinc.net or by request. This product is free of lead and chrome.

Coating performance is dependent on adequate surface preparation and proper application. The information contained in this bulletin is correct to the best of our knowledge. The recommendations and suggestions herein are made without guarantee or representation as to the end result, since the conditions of use are not known and beyond our control. Such information is subject to change and pertains only to the product offered for sale at the time of publication. The user is encouraged to test the complete coating system for adhesion and compatibility prior to full-scale production.

Warranty and limitation of Seller's liability: PFI, Inc. warrants only that the products represented herein meet the formulation standards of PFI, Inc. This warranty shall be in lieu of any other warranty, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. There are no warranties that extend beyond the description on the face hereof. The buyer's sole and exclusive remedy against PFI, Inc. shall be for replacement of the product in the event a defective condition of the product should be found to exist, and the exclusive remedy shall not have failed its essential purpose so long as PFI, Inc. is willing to provide comparable replacement product to the buyer. No other remedy (including but not limited to incidental or consequential damages for lost profits, lost sales, injury to persons or property, environmental injuries, or any other incidental or consequential loss) shall be available to the buyer.



9215 Santa Fe Springs Road
Santa Fe Springs, CA 90670
562-946-6666 | info@pfiinc.net