

SINCE



1952

PAINTS FOR INDUSTRY

ALKYD HARDENER

Significantly enhances the performance properties of Metal-Clad Alkyd Enamels. Shortens dry time while promoting sharper gloss, better color and gloss retention, increased hardness, and improved chemical and abrasion resistance.

- ✓ Improves hardness, gloss, & color retention
- ✓ Increases chemical and abrasion resistance
- ✓ Shortens dry time

DIRECTIONS FOR USE

Use this product ONLY with Metal-Clad Alkyd Enamels. Mix at a ratio of 8:1, with 1 pint of hardener per gallon of paint. Mix thoroughly and let sit for at least five minutes prior to painting.

TECHNICAL DATA

Appearance	Clear
Volume Solids	75%
VOC	262 g/L (2.19 lbs/gal)
Shelf Life	6 months unopened
Packaging	Quart and gallon containers

ADDITIONAL INFORMATION

DANGER: CONTAINS ISOCYANATE. Vapor and spray mist are harmful. Overexposure may cause lung damage and trigger allergic skin and/or respiratory reactions in sensitive people. Isocyanates may affect the brain or other parts of the nervous system, causing nausea, dizziness, or headaches. Wear a properly fitted vapor/particulate respirator equivalent to NIOSH 23C during application and until the work area has been fully exhausted of all vapors. Individuals with chronic respiratory problems should not be exposed to this product's vapor or spray mist. If you experience symptoms, remove to fresh air immediately and contact a physician if breathing difficulty persists or recurs. Follow all applicable directions and use care when handling this product.

Protect this product from moisture to avoid contamination. Moisture will react with the catalyst and decrease its effectiveness.

This product is intended for professional industrial use only. Thoroughly review the product label and Safety Data Sheet before using. Product information, including the SDS and a copy of this PDS is available online at www.pfiinc.net or by request. This product is free of lead and chrome.

Warranty and limitation of Seller's liability: PFI, Inc. warrants only that the products represented herein meet the formulation standards of PFI, Inc. This warranty shall be in lieu of any other warranty, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. There are no warranties that extend beyond the description on the face hereof. The buyer's sole and exclusive remedy against PFI, Inc. shall be for replacement of the product in the event a defective condition of the product should be found to exist, and the exclusive remedy shall not have failed its essential purpose so long as PFI, Inc. is willing to provide comparable replacement product to the buyer. No other remedy (including but not limited to incidental or consequential damages for lost profits, lost sales, injury to persons or property, environmental injuries, or any other incidental or consequential loss) shall be available to the buyer.



9215 Santa Fe Springs Road
Santa Fe Springs, CA 90670
562-946-6666
info@pfiinc.net